

Korean Made Quality				16 Channel
Video / Loop Out				16/16
Monitor Out		1CH Composite, S-video		
VGA Out		1CH		
Spot Out		2CH		
Compression		H.264		
Audio In / Out		4in / 1out(G.723 Compression)		
Record	Speed	NTSC		480Fps
		PAL		400Fps
Play / back	Speed	NTSC		480Fps
		PAL		400Fps
OS		Embedded Linux		
Pentaplex		Surveillance, Recording, Playback, Networking, Backup at the same time		
Network	Interface	10/100 BaseT(1EA)		
	Protocol	TCP/IP(DHCP, Static IP), PPPoE		
	Program	REMOTE, CMS, AGENT, PDA, WEB		
	Transmission speed	Max. 480Fps		
Backup	Installation	USB2.0(3), DVR-RW, Network backup		
	External device	-		
	File	AVI, Readable format		
HDD		Max. 4EA HDD		
Console		RS-232C		
PTZ		RS-485		
Sensor (In/Output)		4/4	8/4	16/4
Control Unit		Front button, Mouse ID Remote Controller(Max. 99EA)		
OSD		GUI, Multi-language available		
Dimention		435(W) X 425(D) X 87(H) mm		
Operation temperature		0~45'c		
Operation humidity		5~85%		
Weight		7kg(Without DVD-RW, HDD)		
Power		AC115/230VAC, 60/50Hz		