

<b>60m IR Illuminated</b>	<b>Weatherproof Camera</b>				
Image Sensor	1/3" SONY ICX639BK CCD				
Horizontal Resolution	600TV Lines Low Illumination, DWDR, OSD				
Pixels	PAL:795 (H)× 596(V) NTSC :811 (H) ×508 (V)				
Usable Illumination	0.001 Lux/F2.0				
TV System	PAL/NTSC				
IR LED	φ 5X72PCS				
IR Series Distance	60 M				
Lens	4-9mm Manual Zoom Lens				
Sync System	Internal				
IR Status	Under 10 Lux By CDS				
IR Power On	CDS Auto Control				
S/N Ratio	≥54dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10℃ ~ +50℃ RH95% Max				
Storage Temperature	-20℃ ~ +60℃ RH95% Max				
White Balance	Auto				
Power Source	DC12V 300mA				
Dimension	255W)×110(H)×105(D)mm				
Weight	1.6Kg				